Application No. 10/549,503

January 9, 2008

Reply to the Office Action dated October 10, 2007

Page 2 of 12

## **AMENDMENTS TO THE SPECIFICATION:**

Please REPLACE the Title of the Invention with the following amended Title of the Invention:

## DEVICE INCORPORATING THE SAME DEVICE AND DISPLAY DEVICE INCORPORATING THE SAME

85

Please REPLACE the first paragraph on page 34 of the Substitute Specification with the following amended paragraph:

The display device of the present embodiment includes a light absorbing layer 5, electrodes 3b, a conversion layer 2, a dimming layer 1, electrodes 3a, and color filters 6 layered in this order on a substrate 34. As shown in FIG. 18, the electrodes 3b include a plurality of patterns extending in parallel, whereas the electrodes 3a include a plurality of patterns extending in a direction perpendicular to the electrodes 3b. An appropriate voltage can be applied to each pair of electrodes 3a, 3b. However, it would also be possible to simply short-circuit the electrodes 3a and electrodes 3b as necessary. The color filters 6 include a plurality of patterns extending substantially in parallel to the electrodes 3a. Among these patterns, typically three patterns of R(red), G(green), and B(blue) are formed for each pixel.

Please REPLACE the paragraph bridging pages 88 and 89 of the Substitute Specification with the following amended paragraph:

The light absorbing layer 5 is formed on the substrate <u>44</u>. The light absorbing layer 5 may be a layer (black) that absorbs light in the entire visible light region, or a layer (any other color) that absorbs light in a part of the visible light region. The formation of the light absorbing

Int